



**8oz. TUBE SEALANT  
10003**

**PREVENT & REPAIR FLAT TIRES**



- **SEALS INSTANTLY**
- **WORKS CONTINUOUSLY FOR 2 YEARS**
- **COMPATIBLE WITH SCHRADER VALVES AND REMOVABLE PRESTA VALVES**
- **NON-FLAMMABLE & NON-TOXIC**



**AVAILABLE NOW**

<b>8oz. Tube Sealant</b>			
PART# 10003    REV082417ART* / REV K**			
	<b>EA.</b>	<b>DIMENSIONS</b>	<b>UPC/CASE CODE</b>
<b>UNIT</b>	1	8.250" H x 1.750" W x 1.750" D • 0.660 LBS	716281000645
<b>MASTER</b>	6	9.125" H x 4.375" W x 6.250" L • 4.159 LBS	10716281008273

U.S. Patent # 7,388,041

ITW Global Tire Repair • 125 Venture Drive, Suite 210, San Luis Obispo, CA 93401 • PHONE: 805.489.0490 • FAX: 805.489.1920  
ITW Global Tire Repair, GmbH • Carl-Benz Str. 10, 88696, Owingen, Germany • PHONE: +49-7551-9200-0 • FAX: +49-7551-9200-990



**WWW.SLIME.COM**

10003\_REV082417\_REVK\_1



# 8oz. TUBE SEALANT 10003 SPEC SHEET

**CONTAINS:**

• 8oz. Tube Sealant 1.750in. x 1.750in. x 8.250 in. (44.45mm x 44.45mm x 209.55mm)

VALVE CORE  
REMOVAL TOOL



**\*ART REVISION CHANGES:**  
REV082417 • Updated label design.

**\*\*REVISION CHANGES:**  
REV A • Initial Release.  
REV B • Change sealant used from 100002 to 100009.  
REV C • Removed tray and lid and replaced with RSC.  
REV D • Change sealant used from 100009 to 100002.  
REV E • Added part number 12000 to BOM at 2 each.  
REV F • Changed formula from 100002 to 100042.  
REV G • Updated art and revised instructions.  
REV H • TM added to logo and Green Promise, R added to Fibro-Seal Technology, revised usage chart and instructions, changed address to SLO, ITW Legal Statement, Changed 8oz 237mL vertical type to 4oz 118mL.  
REV I • Updated BOM to correct location in JDE and updated art to new design and compliance.  
REV J • Box specification change to 200lb mullen test strength to 32ECT.  
REV K • Change to RRP box. Revert back to 200lb mullen board.

## LINKS

[PRODUCT WEB PAGE](#)

[SDS SHEET](#)

[HI RES IN & OUT OF PACKAGE SHOTS,  
6-SIDED PHOTOS, INSTRUCTIONS & UPC](#)

[VIDEO \(N/A\)](#)

[PRODUCT WARRANTY](#)


PART #10003



## ADDITIONAL SET UP INFO

BLENDING AND BOTTLED IN USA

**PALLET INFORMATION:**  
CASES PER LAYER (TIE): 66  
LAYERS PER LOAD (HIGH): 5  
INNER CASES PER PALLET: 330  
EACHES PER PALLET: 1980



ITW Global Tire Repair • 125 Venture Drive, Suite 210, San Luis Obispo, CA 93401 • PHONE: 805.489.0490 • FAX: 805.489.1920  
ITW Global Tire Repair, GmbH • Carl-Benz Str. 10, 88696, Owingen, Germany • PHONE: +49-7551-9200-0 • FAX: +49-7551-9200-990



**WWW.SLIME.COM**

10003\_REV082417\_REVK\_2