



# 24oz. TIRE SEALANT 10008

## PREVENT & REPAIR FLAT TIRES



- SEALS INSTANTLY
- SAFE FOR FINISHED METAL WHEELS
- NON-FLAMMABLE & NON-TOXIC
- TPMS SAFE & APPROVED



### MOWER/ATV



### AVAILABLE NOW

24oz. Tire Sealant			
PART# 10008    REV082417ART* / REV J**			
	EA.	DIMENSIONS	UPC/CASE CODE
UNIT	1	10.000" H x 1.840" W x 1.840" D • 1.840 LBS	716281000690
MASTER	6	11.403" H x 6.375" W x 9.000" L • 11.403 LBS	10716281008334

U.S. Patent # 7,388,041

ITW Global Tire Repair • 125 Venture Drive, Suite 210, San Luis Obispo, CA 93401 • PHONE: 805.489.0490 • FAX: 805.489.1920  
ITW Global Tire Repair, GmbH • Carl-Benz Str. 10, 88696, Owingen, Germany • PHONE: +49-7551-9200-0 • FAX: +49-7551-9200-990



[WWW.SLIME.COM](http://WWW.SLIME.COM)

10008\_REV082417\_REV\_1



# 24oz. TIRE SEALANT 10008 SPEC SHEET

**CONTAINS:**

• 24oz. Tire Sealant 1.840in. x 1.840in. x 10.000in. (63.5mm x 63.5mm x 234.95mm)

VALVE CORE  
REMOVAL TOOL

FLEX TUBE



**\*ART REVISION CHANGES:**  
REV082417 • Updated label design.

**\*\*REVISION CHANGES:**

- REV A • Replace 100218 cap with 60051 cap..
- REV B • Change BOM to be made off site.
- REV C • Change BOM to include new inner case box.
- REV D • Change sealant and labor to be produced domestically.
- REV E • Added part number 12000 to BOM at 2 each.
- REV F • Updated art and revised instructions.
- REV G • TM added to Slime Logo and Green Promise Logo. R added to Fibro-Seal Technology. Revised instruction verbiage. Changed address to SLO. ITW Legal Statement. Change wording "Not to clog TPMS" statement.
- REV H • Change SDS sealant sku to TPMS & updated part description.
- REV I • Update manufacturing location/warehouse and updated art to new design. Updated compliance.
- REV J • Updated box to RRP and added art to box. Reverted back to 200lb mullen board.

## LINKS

[PRODUCT WEB PAGE](#)

[SDS SHEET](#)

[HI RES IN & OUT OF PACKAGE SHOTS,  
6-SIDED PHOTOS, INSTRUCTIONS & UPC](#)

[VIDEOS](#)

[PRODUCT WARRANTY](#)

**PART #10008**




## ADDITIONAL SET UP INFO

BLENDING AND BOTTLED IN USA

**PALLET INFORMATION:**

CASES PER LAYER (TIE): 30  
 LAYERS PER LOAD (HIGH): 4  
 MASTER CASES PER PALLET: 120  
 EACHES PER PALLET: 720



ITW Global Tire Repair • 125 Venture Drive, Suite 210, San Luis Obispo, CA 93401 • PHONE: 805.489.0490 • FAX: 805.489.1920  
 ITW Global Tire Repair, GmbH • Carl-Benz Str. 10, 88696, Owingen, Germany • PHONE: +49-7551-9200-0 • FAX: +49-7551-9200-990



**WWW.SLIME.COM**

10008\_REV082417\_REV\_2