



16oz. TIRE SEALANT 10183

PREVENT & REPAIR FLAT TIRES



- SEALS INSTANTLY FOR 2 YEARS
- STOPS SLOW LEAKS
- SAFE & EASY



OFF-ROAD



AVAILABLE NOW

16oz. Tire Sealant			
PART# 10183		REV101618ART* / REV A**	
	EA.	DIMENSIONS	UPC/CASE CODE
UNIT	1	9.250" H x 2.5" W x 2.5" D • 1.260 LBS	716281510076
INNER	6	10.000" H x 7.875" W x 5.500" L • 7.892 LBS	10716281510073

U.S. Patent # 7,388,041

ITW Global Tire Repair • 125 Venture Drive, Suite 210, San Luis Obispo, CA 93401 • PHONE: 805.489.0490 • FAX: 805.489.1920
ITW Global Tire Repair, GmbH • Carl-Benz Str. 10, 88696, Owingen, Germany • PHONE: +49-7551-9200-0 • FAX: +49-7551-9200-990



WWW.SLIME.COM

10183_REV101618_REVA_1



16oz. TUBE SEALANT 10183 SPEC SHEET

CONTAINS:

• 16oz. Tire Sealant 2.5in. x 2.5in. x 9.250in. (63.5mm x 63.5mm x 234.95mm)

VALVE CORE
REMOVAL TOOL

FLEX TUBE



*ART REVISION CHANGES:
REV101618 • Initial Release.

**REVISION CHANGES:
REV A • Initial Release.

LINKS

[PRODUCT WEB PAGE](#)

[SDS SHEET](#)

[HI RES IN & OUT OF PACKAGE SHOTS,
6-SIDED PHOTOS, INSTRUCTIONS & UPC](#)

[VIDEOS](#)

[PRODUCT WARRANTY](#)

PART #10183




ADDITIONAL SET UP INFO

BLENDED AND BOTTLED IN USA

PALLET INFORMATION:

CASES PER LAYER (TIE): 43
LAYERS PER LOAD (HIGH): 4
INNER CASES PER PALLET: 172
EACHES PER PALLET: 1032



ITW Global Tire Repair • 125 Venture Drive, Suite 210, San Luis Obispo, CA 93401 • PHONE: 805.489.0490 • FAX: 805.489.1920
ITW Global Tire Repair, GmbH • Carl-Benz Str. 10, 88696, Owingen, Germany • PHONE: +49-7551-9200-0 • FAX: +49-7551-9200-990



WWW.SLIME.COM

10183_REV101618_REVA_2