



27.5" SELF-SEALING PRESTA TUBE 30023

NO MORE FLATS

- INSTANTLY SEALS TREAD AREA PUNCTURES UP TO 3MM FOR UP TO 3 YEARS



PRESTA VALVE



PRESTA 48mm



AVAILABLE NOW			
27.5" Presta Self-Sealing Bike Tube			
PART# 30023		REV080620ART* / REV L**	
	EA.	DIMENSIONS	UPC/CASE CODE
UNIT	1	114.3mm H x 63.50mm W x 101.6mm D • 0.308 kg	402080430027
INNER	5	133.4mm H x 331.8mm W x 115.9mm L • 1.743 kg	14020804300239
MASTER	50	282.6mm H x 339.73mm W x 589mm L • 17.998 kg	24020804300236

UFI: M22X-288M-D00X-FRXG

ITW Global Tire Repair • 125 Venture Drive, Suite 210, San Luis Obispo, CA 93401 • PHONE: 805.489.0490 • FAX: 805.489.1920
 ITW Global Tire Repair, GmbH • Carl-Benz Str. 10, 88696, Owingen, Germany • PHONE: +49-7551-9200-0 • FAX: +49-7551-9200-990



27.5" SELF-SEALING PRESTA TUBE 30023 SPEC SHEET

CONTAINS:

- 27.5in. Self-Sealing Presta Tube 27.5in. x 2.0-2.4in.

PRESTA VALVE



LINKS

[PRODUCT WEB PAGE](#)

[SDS SHEET](#)

[HI RES IN & OUT OF PACKAGE SHOTS,
6-SIDED PHOTOS, INSTRUCTIONS & UPC](#)

[VIDEO \(N/A\)](#)

[PRODUCT WARRANTY](#)

#30023



ADDITIONAL SET UP INFO

HTS CODE: 4013.90.5050
COUNTRY OF ORIGIN: CHINA

PALLET INFORMATION:

CASES PER LAYER (TIE): 4
LAYERS PER LOAD (HIGH): 3
MASTER CASES PER PALLET: 12
INNER CASES PER PALLET: 120
EACHES PER PALLET: 600



***ART REVISION CHANGES:**

REV080620 • Updated dieline to remove hangtab and updated art to mimic domestic packaging.

****REVISION CHANGES:**

REV F • Initial Release.

REV G • Removed "32mm" callout from art. Changed valve length.

REV H • Update presta valve.

REV I • Full color box description added, inner case updated, master case removed, sealant mass called out.

REV K • Adjusted tube size and tube size callout on art.

REV L • Updated package to mimic domestic package, moved instructions to inside of box.

ITW Global Tire Repair • 125 Venture Drive, Suite 210, San Luis Obispo, CA 93401 • PHONE: 805.489.0490 • FAX: 805.489.1920

ITW Global Tire Repair, GmbH • Carl-Benz Str. 10, 88696, Owingen, Germany • PHONE: +49-7551-9200-0 • FAX: +49-7551-9200-990

WWW.SLIME.COM

30023_REV080620_REV_L_2