




# TIRE INFLATOR ANALOG 40050

**CARS • LIGHT TRUCKS • SUVs**



AUTO TIRES



12V

- **PUT ONE IN EVERY VEHICLE**
- **FAST AND EASY TO USE**
- **INFLATE ALL YOUR TOYS**

## AVAILABLE NOW

### Tire Inflator Analog

PART# 40050

REV042518ART / REV B\*\*

	EA.	DIMENSIONS	CASE CODE
<b>UNIT</b>	1	6.125" H x 2.750" W x 8.000" D • 2.10 LBS	716281509162
<b>MASTER</b>	2	6.875" H x 6.063" W x 8.563" L • 4.463 LBS	10716281509169



ITW Global Tire Repair • 125 Venture Drive, Suite 210, San Luis Obispo, CA 93401 • PHONE: 805.489.0490 • FAX: 805.489.1920  
ITW Global Tire Repair, GmbH • Carl-Benz Str. 10, 88696, Owingen, Germany • PHONE: +49-7551-9200-0 • FAX: +49-7551-9200-990



**WWW.SLIME.COM**

40050\_REV042518\_REV\_B\_1




# TIRE INFLATOR ANALOG 40050 SPEC SHEET

**KIT CONTAINS:**

- One (1) Analog Display Inflator 4.92in. x 3.93in. x 1.97in. (125mm x 100mm x 50mm)
- One (1) Inflatable Adapter 1.50in. x 0.355in. x 0.355in. (38.2mm x 9.0mm x 9.0mm)
- One (1) Needle Adapter 1.53in. x 0.3in. x 0.3in. (39mm x 7.62mm x 7.62mm)
- Instruction Booklet

**AIR ADAPTERS****AIR ADAPTER STORAGE**

- Inflatable adapters snap-in-place for easy access

**LINKS**[PRODUCT WEB PAGE](#)[SDS SHEET \(N/A\)](#)[HI RES IN & OUT OF PACKAGE SHOTS, 6-SIDED PHOTOS, INSTRUCTIONS & UPC](#)[VIDEOS](#)[PRODUCT WARRANTY](#)

PART# 40050



7 16281 50916 2


**WARNING: Cancer & Reproductive Harm - www.P65Warnings.ca.gov****ADDITIONAL SET UP INFO**

HTS CODE: 8414.80.1685

COUNTRY OF ORIGIN: CHINA

PALLET INFORMATION:

CASES PER LAYER (TIE): 37  
 LAYERS PER LOAD (HIGH): 7  
 MASTER CASES/PALLET: 259  
 EACHES PER PALLET: 518

**LIGHT**

- Bright LED
- For night-time emergencies

**ON/OFF BUTTON****INFLATOR**

- Compact design
- Air-cooled motor

**POWER SOURCE**

- Plugs into 12V power outlet

**AIR HOSE****DIAL GAUGE**

- 0–100 PSI range
- 0–7 BAR range

TECH SPECS	
IDEAL USES	Tires
TIRE INFLATION TIME	8 min**
CFM	0.49 (13.9 LPM) @ 0 PSI
DIAL GAUGE	0–100 PSI (0–7 BAR)
POWER SOURCE	12V Accessory Power Outlet
POWER CORD LENGTH	10 ft. (3m)
AIR HOSE LENGTH	2 ft. (0.6m)
LIGHT	LED

\* (0–35 PSI, Standard Tire: P195/65 R15)

**\*ART REVISION CHANGES:**

REV042518 • Updated Prop 65 warning.

**\*\*REVISION CHANGES:**

REV A • Initial Release.

REV B • Updated Prop 65 warning. Updated gauge face.

ITW Global Tire Repair • 125 Venture Drive, Suite 210, San Luis Obispo, CA 93401 • PHONE: 805.489.0490 • FAX: 805.489.1920  
 ITW Global Tire Repair, GmbH • Carl-Benz Str. 10, 88696, Owingen, Germany • PHONE: +49-7551-9200-0 • FAX: +49-7551-9200-990

**WWW.SLIME.COM**

40050\_REV042518\_REV\_2