



DUAL POWER TIRE INFLATOR 40052



HOME 120V • AUTO 12V



AUTO TIRES




BICYCLE TIRES




FLOATIES



SPORTS BALLS



120V



12V

- EASY READ DIGITAL DISPLAY
- QUICK INFLATION
- INFLATE-RIGHT™ TECHNOLOGY
Auto Shutoff at Set Pressure



AVAILABLE NOW

Dual Power Tire Inflator			
PART# 40052		REV041619ART* / REV A**	
	EA.	DIMENSIONS	CASE CODE
UNIT	1	9.095" H × 6.180" W × 6.420" D • 4.726 LBS	716281509230
MASTER	2	9.813" H × 12.875" W × 6.938" L • 10.076 LBS	10716281509237

ITW Global Tire Repair • 125 Venture Drive, Suite 210, San Luis Obispo, CA 93401 • PHONE: 805.489.0490 • FAX: 805.489.1920
 ITW Global Tire Repair, GmbH • Carl-Benz Str. 10, 88696, Owingen, Germany • PHONE: +49-7551-9200-0 • FAX: +49-7551-9200-990



DUAL POWER TIRE INFLATOR 40052 SPEC SHEET

KIT CONTAINS:

- One (1) Dual Power Inflator 7in. x 4.3in. x 4.3in. (178mm x 109mm x 109mm)
- One (1) Small Inflatable Adapter 1.50in. x 0.355in. x 0.355in. (38.2mm x 9.0mm x 9.0mm)
- One (1) Large Inflatable Adapter 1.07in. x 0.32in. x 0.32in. (27.2mm x 8.12mm x 8.12mm)
- One (1) Needle Adapter 1.53in. x 0.3in. x 0.3in. (39mm x 7.62mm x 7.62mm)
- Two (2) 1.5in. (38mm) Mounting Screws with Wall Anchors
- Instruction Booklet



LINKS

[PRODUCT WEB PAGE](#)

[SDS SHEET \(N/A\)](#)

[HI RES IN & OUT OF PACKAGE SHOTS,
6-SIDED PHOTOS, INSTRUCTIONS & UPC](#)

[VIDEOS](#)

[PRODUCT WARRANTY](#)

PART# 40052



WARNING: Cancer & Reproductive Harm - www.P65Warnings.ca.gov


ADDITIONAL SET UP INFO

HTS CODE: 8414.80.1685

COUNTRY OF ORIGIN: CHINA

PALLET INFORMATION:

CASES PER LAYER (TIE): 20
LAYERS PER LOAD (HIGH): 5
MASTER CASES/PALLET: 100
EACHES PER PALLET: 200



TECH SPECS

TIRE INFLATION TIME	6 min*
CFM	0.58 (16.4 LPM)
DIGITAL GAUGE	0-99 PSI
POWER SOURCE	12V Accessory Power Outlet
POWER SOURCE	120V Wall Outlet
12V POWER CORD LENGTH	9.67 ft. (294.7cm)
120V POWER CORD LENGTH	36 in. (91cm)
AIR HOSE LENGTH	2.46 ft. (75cm)
TOTAL REACH	12V: 12 ft. (365cm) / 120V: 5.45 ft. (166cm)
REPLACEABLE FUSE	12V: 15A 250V 5mm x 20mm 120V: 2A 250V 5mm x 20mm

* (0-35 PSI, Standard Tire: P195/65 R15)

*ART REVISION CHANGES:
REV041619 • Initial release.

**REVISION CHANGES:
REV A • Initial Release.

ITW Global Tire Repair • 125 Venture Drive, Suite 210, San Luis Obispo, CA 93401 • PHONE: 805.489.0490 • FAX: 805.489.1920

ITW Global Tire Repair, GmbH • Carl-Benz Str. 10, 88696, Owingen, Germany • PHONE: +49-7551-9200-0 • FAX: +49-7551-9200-990