



COMPACT INFLATOR 40060

CARS • TRUCKS • BIKES • INFLATABLES




AUTO TIRES



BIKE TIRES

-  Checks Pressure
-  Illuminates Work Area
-  Airs Up



AVAILABLE NOW

Compact Inflator			
PART# 40060		REV062019ART / REV B**	
	EA.	DIMENSIONS	CASE CODE
UNIT	1	6.800" H x 2.620" W x 5.800" D • 1.830 LBS	716281509810
INNER	2	7.125" H x 5.563" W x 6.125" D • 3.825 LBS	10716281509817
MASTER	12	7.875" H x 17.250" W x 12.813" L • 23.998 LBS	20716281509814

 **10** MINUTES
FLAT to FULL
*Standard Car Tire

ITW Global Tire Repair • 125 Venture Drive, Suite 210, San Luis Obispo, CA 93401 • PHONE: 805.489.0490 • FAX: 805.489.1920
ITW Global Tire Repair, GmbH • Carl-Benz Str. 10, 88696, Owingen, Germany • PHONE: +49-7551-9200-0 • FAX: +49-7551-9200-990

WWW.SLIME.COM

40060_REV062019_REV B_1



COMPACT INFLATOR 40060 SPEC SHEET

KIT CONTAINS:

- One (1) Analog Display Inflator 6.30in. x 5.12in. x 2.36in. (160mm x 130mm x 60mm)
- One (1) Inflatable Adapter 1.50in. x 0.355in. x 0.355in. (38.2mm x 9.0mm x 9.0mm)
- One (1) Needle Adapter 1.53in. x 0.3in. x 0.3in. (39mm x 7.62mm x 7.62mm)
- Instruction Booklet

LIGHT

- Bright LED
- For night-time emergencies

ON/OFF BUTTON

INFLATOR

- Compact design

POWER SOURCE

- Plugs into 12V power outlet



AIR ADAPTER STORAGE

- Inflatable adapters snap-in-place for easy access



DIAL GAUGE

- 0-100 PSI range
- 0-7 BAR range



AIR ADAPTERS

QUICK CONNECT AIR HOSE

LINKS

[PRODUCT WEB PAGE](#)

[SDS SHEET \(N/A\)](#)

[HI RES IN & OUT OF PACKAGE SHOTS, 6-SIDED PHOTOS, INSTRUCTIONS & UPC](#)

[VIDEOS](#)

[PRODUCT WARRANTY](#)

PART# 40060




ADDITIONAL SET UP INFO

HTS CODE: 8414.80.1685

COUNTRY OF ORIGIN: CHINA

PALLET INFORMATION:

CASES PER LAYER (TIE): 8
 LAYERS PER LOAD (HIGH): 6
 MASTER CASES/PALLET: 48
 INNER CASES/PALLET: 288
 EACHES PER PALLET: 576



TECH SPECS

TIRE INFLATION TIME	10 min**
CFM (LPM)	0.44 (12.5 LPM) @ 0 PSI/BAR
DIAL GAUGE	0-100 PSI (0-7 BAR)
POWER SOURCE	12V Accessory Power Outlet
POWER CORD LENGTH	9.7 ft. (2.95m)
REPLACEABLE FUSE	15A 250V 5mm x 20mm
AIR HOSE LENGTH	19.5 in. (0.5m)
TOTAL REACH	11.3 ft. (3.45m)
LIGHT	7 Lumens

* (0-35 PSI, Standard Tire: P195/65 R15)

*ART REVISION CHANGES:

REV062019 • Updated dieline for hangtab. Updated marketing callouts.

**REVISION CHANGES:

REV A • Initial Release.

REV B • Updated hangtab for strength, updated art/callouts.

ITW Global Tire Repair • 125 Venture Drive, Suite 210, San Luis Obispo, CA 93401 • PHONE: 805.489.0490 • FAX: 805.489.1920

ITW Global Tire Repair, GmbH • Carl-Benz Str. 10, 88696, Owingen, Germany • PHONE: +49-7551-9200-0 • FAX: +49-7551-9200-990