



**TRUCK SPAIR
50063**

EMERGENCY FLAT TIRE REPAIR



 **ALL TIRES**

- 16 PIECE KIT
- 3 MINUTES TO INFLATE,
11 MINUTES TO REPAIR
- ALTERNATIVE TO A
SPARE TIRE

AVAILABLE NOW

Truck Spair			
PART# 50063		REV042418ART* / REV E**	
	EA.	DIMENSIONS	UPC/CASE CODE
UNIT	1	9.875" H x 4.750" W x 13.250" D • 8.500 LBS	716281503368
MASTER	2	11.375" H x 10.000" W x 13.810" L • 17.707 LBS	10716281503365

ITW Global Tire Repair • 125 Venture Drive, Suite 210, San Luis Obispo, CA 93401 • PHONE: 805.489.0490 • FAX: 805.489.1920
ITW Global Tire Repair, GmbH • Carl-Benz Str. 10, 88696, Owingen, Germany • PHONE: +49-7551-9200-0 • FAX: +49-7551-9200-990



WWW.SLIME.COM

500063_REV042418_REVE_1



TRUCK SPAIR 50063 SPEC SHEET

KIT CONTAINS:

- One (1) Inflator 9.5in. x 5.25in. x 4.3in. (241mm x 133 mm x 109mm)
- One (1) Inflatable Adapter 1.43in. x 0.32in. x 0.32in. (36.3mm x 8.12mm x 8.12mm)
- One (1) Inflatable Adapter 1.07in. x 0.32in. x 0.32in. (27.2mm x 8.12mm x 8.12mm)
- One (1) Needle Adapter 1.53in. x 0.3in. x 0.3in. (39mm x 7.62mm x 7.62mm)
- One (1) Extension Coil Air Hose 177in. x 0.6in. x 0.6in. (4496mm x 15.2mm x 15.2mm)
- One (1) Replacement Fuse 1.2in. x 0.25in. x 0.25in. (30.5mm x 6.35mm x 6.35mm)
- One (1) Pencil Gauge 6in. x 0.6in. x 0.5in. (152mm x 15.2mm x 12.7mm)
- One (1) Valve Core Removal Tool 2in. x 1in. x 0.25in. (50.8mm x 25.4mm x 6.35mm)
- Two (2) Replacement Valve Cores 0.75in. x 0.13in. x 0.13in. (19.1mm x 3.3mm x 3.3mm)
- Four (4) Aluminum Valve Caps 0.67in. x 0.48in. x 0.48in. (16.9mm x 12.2mm x 12.2mm)
- One (1) Pro Power Alligator Clips 95.5in. x 2.5in. x 0.5in. (2426mm x 63.5mm x 12.7mm)
- One (1) Bottle 24 fl.oz./710 mL Slime Sealant 10in. x 2.8in. x 2.8in. (254mm x 71.1mm x 71.1mm)
- Instruction Booklet

LINKS

[PRODUCT WEB PAGE](#)

[SDS SHEET](#)

[HI RES IN & OUT OF PACKAGE SHOTS,
6-SIDED PHOTOS, INSTRUCTIONS & UPC](#)

[VIDEOS](#)

[PRODUCT WARRANTY](#)

PART #50063



WARNING: Cancer & Reproductive Harm - www.P65Warnings.ca.gov


ADDITIONAL SET UP INFO

HTS CODE: 8414.80.1685

COUNTRY OF ORIGIN: CHINA

PALLET INFORMATION:

CASES PER LAYER (TIE): 12
LAYERS PER LOAD (HIGH): 5
MASTER CASES/PALLET: 60
EACHES PER PALLET: 120



EASY GRAB HANDLE



INFLATOR

- Powerful direct-drive motor
- Thermal break safety feature
- Air-cooled motor

EMERGENCY TIRE SEALANT

- Seals instantly
- No jack needed
- Safe and easy
- Tire sensor safe



EXTENSION COIL AIR HOSE

- Connect to built-in air hose for extra reach
- Twist-tight valve

DIAL GAUGE

- Integrated in air hose
- Shock-resistant housing
- 0-150 PSI range
- 0-10 BAR range

POWER SOURCE

- Plugs into 12V power outlet

AIR ADAPTERS



VALVE CORES



ALUMINUM VALVE CAPS



PENCIL GAUGE



VALVE CORE REMOVAL TOOL



PRO POWER ALLIGATOR CLIPS

- For a direct to battery connection

*ART REVISION CHANGES:

REV042418 • Updated design to be consistent with spair line and to be compliant.

**REVISION CHANGES:

REV A • Initial Release.

REV B • Changed inflator to shorter handle, removed switch, changed hose to braid. Changed packaging to new spair like design.

REV C • Updated inflator to new inflator design. Updated packaging to new look and feel. Changed valve caps from green to silver.

REV D • Changed rubber handle on bag to cloth handle.

REV E • Added Prop 65 warning, updated company name. Updated fuse and removed Slime stickers.



ITW Global Tire Repair • 125 Venture Drive, Suite 210, San Luis Obispo, CA 93401 • PHONE: 805.489.0490 • FAX: 805.489.1920

ITW Global Tire Repair, GmbH • Carl-Benz Str. 10, 88696, Owingen, Germany • PHONE: +49-7551-9200-0 • FAX: +49-7551-9200-990



WWW.SLIME.COM

500063_REV042418_REV_2