



**SMART SPAIR
50107**

EMERGENCY FLAT TIRE REPAIR KIT



CAR / TRAILER



REFILL WITH
PART# 10011 OR #10012



- NO JACK OR TOOLS NEEDED
- 4 SIMPLE STEPS
- BACK ON THE ROAD IN 15 MINUTES

AVAILABLE NOW

Smart Spair

PART# 50107

REV012820ART* / REV C**

	EA.	DIMENSIONS	UPC/CASE CODE
UNIT	1	6.750" H x 2.875" W x 8.250" D • 2.710 LBS	716281507731
MASTER	3	7.125" H x 9.000" W x 8.625" L • 8.446 LBS	10716281507738

ITW Global Tire Repair • 125 Venture Drive, Suite 210, San Luis Obispo, CA 93401 • PHONE: 805.489.0490 • FAX: 805.489.1920
ITW Global Tire Repair, GmbH • Carl-Benz Str. 10, 88696, Owingen, Germany • PHONE: +49-7551-9200-0 • FAX: +49-7551-9200-990



WWW.SLIME.COM

50107_REV012820_REV_C_1



SMART SPAIR 50107 SPEC SHEET

KIT CONTAINS:

- One (1) Analog Display Inflator 6.3in. x 5.12in. x 2.36in. (160mm x 130mm x 60mm)
- One (1) Bottle 16fl. oz/473mL Slime Sealant 2.75in. x 2.75in. x 6.5in. (69.85mm x 69.85mm x 165.1mm)
- One (1) Inflatable Adapter 1.50in. x 0.355in. x 0.355in. (38.2mm x 9.0mm x 9.0mm)
- One (1) Needle Adapter 1.53in. x 0.3in. x 0.3in. (39mm x 7.62mm x 7.62mm)
- One (1) Cap Tool 1.18in. x 1.18in. x 2.05in. (30mm x 30mm x 52mm)
- Instruction Booklet

ADAPTER STORAGE ON BACK OF INFLATOR

- Inflatable adapters snap-in-place for easy access

LIGHT

- Bright LED for night-time emergencies

DIAL GAUGE

- 0-100 PSI range

ON/OFF SWITCH

POWER SOURCE

- Plugs into 12V power outlet

QUICK CONNECT AIR HOSE

EMERGENCY TIRE SEALANT

- Valve Core Tool & Filler Cap Included



AIR ADAPTERS FILLER CAP/TOOL

LINKS

[PRODUCT WEB PAGE](#)

[SDS SHEET](#)

[HI RES IN & OUT OF PACKAGE SHOTS, 6-SIDED PHOTOS, INSTRUCTIONS & UPC](#)

[VIDEOS](#)

[PRODUCT WARRANTY](#)

PART# 50107



WARNING: Cancer & Reproductive Harm - www.P65Warnings.ca.gov


ADDITIONAL SET UP INFO

HTS CODE: 8414.80.1685

COUNTRY OF ORIGIN: CHINA

PALLET INFORMATION:

CASES PER LAYER (TIE): 20
 LAYERS PER LOAD (HIGH): 6
 MASTER CASES/PALLET: 120
 EACHES PER PALLET: 360



TECH SPECS

TIRE INFLATION TIME	10 min*
CFM (LPM)	0.44 (12.5 LPM) @ 0 PSI
DIAL GAUGE	0-100 PSI (0-7 BAR)
POWER SOURCE	12V Accessory Power Outlet
POWER CORD LENGTH	9.7 ft. (2.95 m)
AIR HOSE LENGTH	19.5 in. (0.5 m)
TOTAL REACH	11.3 ft. (3.45 m)
REPLACEABLE FUSE	15A 250V 5mm x 20mm
LED LIGHT	7 Lumens

* (0-35 PSI, Standard Tire: P195/65 R15)

*ART REVISION CHANGES:

REV012820 • Updated dieline and design to be consistent with emergency repair family.

**REVISION CHANGES:

REV A • Initial Release.

REV B • Changed inflator to compact. Updated art.

REV C • Updated art. Updated COO location for compliance.

ITW Global Tire Repair • 125 Venture Drive, Suite 210, San Luis Obispo, CA 93401 • PHONE: 805.489.0490 • FAX: 805.489.1920

ITW Global Tire Repair, GmbH • Carl-Benz Str. 10, 88696, Owingen, Germany • PHONE: +49-7551-9200-0 • FAX: +49-7551-9200-990



WWW.SLIME.COM

50107_REV012820_REV_2