



FLAT TYRE REPAIR KIT DIAL 50129

EMERGENCY REPAIR WITH THE PUSH OF A BUTTON



- NO JACK OR TOOLS NEEDED
- 1 SIMPLE STEP
- BACK ON THE ROAD IN 10 MINUTES

REFILL AVAILABLE
PART# 10180



AVAILABLE NOW

Flat Tyre Repair Kit Dial			
PART# 50129		REV111120ART* / REV C**	
	EA.	DIMENSIONS	UPC/CASE CODE
UNIT	1	206.4mm H x 76.2mm W x 254.0mm D • 1.452 kg	716281509759
MASTER	2	225.4mm H x 166.7mm W x 268.3mm D • 3.07 kg	10716281509756

UFI: KRAS-YD12-4F0E-GJP8

ITW Global Tire Repair • 125 Venture Drive, Suite 210, San Luis Obispo, CA 93401 • PHONE: 805.489.0490 • FAX: 805.489.1920

ITW Global Tire Repair, GmbH • Carl-Benz Str. 10, 88696, Owingen, Germany • PHONE: +49-7551-9200-0 • FAX: +49-7551-9200-990



FLAT TYRE REPAIR KIT DIAL 50129 SPEC SHEET

KIT CONTAINS:

- One (1) Analog Display Inflator 228.6mm × 196.85mm × 76.2mm
- One (1) Bottle 15fl. oz/450mL Slime Sealant 212.73mm × 69.85mm × 47.63mm
- One (1) Inflatable Adapter 38.2mm × 9.0mm × 9.0mm
- One (1) Needle Adapter 39mm × 7.62mm × 7.62mm
- One (1) Presta Valve Adapter 10mm × 10mm × 19mm
- One (1) Valve Depressor 12mm × 12mm × 18mm
- Instruction Booklet

SELECT MODE
AIR OR
AIR + SEALANT

REPLACEABLE SLIME SEALANT
CARTRIDGE #10180

ON/OFF



DIAL GAUGE
• Measures PSI/BAR

PRESSURE RELEASE
• Deflate tire if it has
too much air



ADAPTERS



SEALANT/
AIR HOSE

POWER SOURCE

- Plugs into 12 volt,
15 amp power outlet
- 13.94ft. (4.25m) length

LINKS

[PRODUCT WEB PAGE](#)

[SDS SHEET](#)

[HI RES IN & OUT OF PACKAGE SHOTS,
6-SIDED PHOTOS, INSTRUCTIONS & UPC](#)

[VIDEOS](#)

[PRODUCT WARRANTY](#)

PART #50129



7 16281 50975 9




ADDITIONAL SET UP INFO

HTS CODE: 8414.80.1685

COUNTRY OF ORIGIN: CHINA

PALLET INFORMATION:

CASES PER LAYER (TIE): 25
LAYERS PER LOAD (HIGH): 5
MASTER CASES/PALLET: 125
EACHES PER PALLET: 250



*ART REVISION CHANGES:

REV0111120 • Updated warnings to V1D and updated compliant.

**REVISION CHANGES:

REV A • Initial Release.

REV B • Added distance verbiage, bottle changed to PMS 368
Green, Added UFI Code.

REV C • Transitioned to V1D sealant, updated warnings to be
compliant.

ITW Global Tire Repair • 125 Venture Drive, Suite 210, San Luis Obispo, CA 93401 • PHONE: 805.489.0490 • FAX: 805.489.1920

ITW Global Tire Repair, GmbH • Carl-Benz Str. 10, 88696, Owingen, Germany • PHONE: +49-7551-9200-0 • FAX: +49-7551-9200-990

WWW.SLIME.COM

50129_REV111120_REV_C_2